

3652RK

Creative Touch 3 Series 65" Interactive Flat Panel Display



- Create, connect and collaborate effortlessly with Creative Board Ready-to-use whiteboard featuring builtin annotation tools
- Advanced touch technology Pen and finger recognition for a seamless experience
- Designed for hybrid learning Teach and collaborate from separate locations in real-time
- Safe and secure viewing experience Anti-glare, anti-fingerprint, low blue light and flicker free TUV certified panel

Robust collaboration, extensive connectivity options and a value-focused design. Combining the latest technology and packed with everything a classroom or business requires, the Creative Touch 3 Series delivers all the functionalities and processing power needed to create, educate and collaborate.

Easily access the front-facing ports for HDMI and USB connectivity. For wireless connectivity, CreativeCast Pro™ allows up to four users to share contents at the same time from their Windows, iOS, macOS, Chrome or Android device.

In order to let teachers can now work on their lesson plans from home and instantly bring them to any classroom, our Creative Board includes Google Classroom with single sign-on (SSO) design, teachers can quickly sync with Google Classroom bringing the benefits of paperless sharing and digital collaboration to the classroom. Furthermore, the easy-to-use IFPDs also make lessons more fun with built-in collaboration tools such as Vote, where teachers are able to collect valuable feedback instantly.

Remotely manage your IFPDs, projectors, LED displays and more. Set alerts, schedule tasks or settings and broadcast announcements. Optoma's Management Suite (OMS)™ solution is perfect for easy management and control from any location for all your compatible Optoma devices.



Specifications

Display Back light	Direct type LED
Size (diagonal)	65"
Resolution	3840 x 2160 (UHD 4K)
Brightness	400
Contrast ratio	5.000:1
Viewing angle	178°
Response time	8ms
Life	8ms 50,000 hours
≤ne Speaker count	2
Watts per speaker	2 20W
Glass	2000 4 mm Tempered Glass with Anti Glare + Anti Fingerprint
Ambient light sensor	4 mm rempered diass with Anti diare + Anti Fingerprint Yes
Touch resolution	32768 x 32768
Physical spec	02100 X 02100
Physical spec Dimensions (W x D x H)	1640 x 1036 x 207
Wall-hanging screw spec	M8*25mm
/ESA holes	600x400
n the box	Power Cord
In the box	Remote Control
	Quick Start Guide
	USB Cable
	HDMI Cable
	Writing Pen x 2
Connections	Inputs 3 x HDMI 2.0, 1 x VGA, 1 x Audio 3.5mm, 1 x S/PDIF, 3 x USB 2.0, 2 x USB 3.0, 1 x USB-C, 1 x RJ45, 1 x
	DisplayPort, 1 x Mic 3.5mm
	Outputs 1 x HDMI 2.0, 1 x Audio 3.5mm, 1 x RJ45
	Control 2 x USB Touchport, 1 x RS232
ezel size (top)	17.70mm
ezel size (bottom)	45.70mm
lezel size (left)	17.70mm
ezel size (right)	17.70mm
Operating conditions	20% ~ 93% RH
Dperating temperature (min)	-10°C
Dperating temperature (max)	45°C
Vet weight	43 O 39 kg
Gross weight	50 kg
ouch system	00 MA
ystem	Windows10/Windows11/Linux/Mac (1 Touch point
	only)/Android/Chrome
ouch accuracy	<1.00mm
ouch point	Up to 20 points touch
ouch tool	Finger, Passive infrared pen
en/finger detection	Yes
Power	
Power supply	AC 100-240V, 50/60 Hz
Power consumption (standby)	0.5W
Power consumption (max)	300W
Dperation System	
System version	Android 11.0
PU	Quad-core
aPU	Dual-core
	4GB
	4GD
RAM	
RAM Storage OSD / display languages	4GD 32GB 17 languages: Arabic, Czech, Danish, Dutch, English, French, German, Italian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),



Copyright © 2023, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 05072023033049