

# CinemaX D2+

4K UHD ultra short throw laser home projector



- **Breathtaking 4K UHD resolution with Laser Light Source**
- **Ultra short throw feature, 120" big screen in inches away**
- **Bright 3,000 lumens and stable output, achieves 1,800,000 : 1 Contrast.**
- **Superb gaming experience with extremely low 4ms Input Lag for 240Hz at 1080P**



CinemaX D2+ features 4K UHD resolution and supports eARC audio, offering the ultimate cinematic experience like no other. The ultra short throw technology allows you to enjoy up to 120" screen in just inches away. With Amazing Color and 121% of Rec.709 gamut coverage, D2+ can deliver richer color performance and makes pictures even more realistic.

## Specifications

<b>Display and image</b>	
ProjDisplayTechnology	DLP™
ProjNativeResolution	UHD (3840x2160)
ProjBrightnessBrightLumens	3.000
ProjContrastRatio	1.800.000
NativeAspectRatio	16:9
SupportedAspectRatio	4:3, 16:9, 16:10
ProjKeystoneCorrectionHorizontal	10°
ProjKeystoneCorrectionVertical	10°
ProjHorizontalScanRateKhz	31 ~ 135
ProjVerticalScanRateHz	24 ~ 120
ProjUniformityPercent	90
Screen size	2.16m ~ 3.05m (85" ~ 120") diagonal
<b>Lamp info</b>	
ProjLightSource	Laser
ProjLaserHours	30.000
<b>Optical</b>	
ThrowRatio	0.25:1
ProjectionDistanceMetres	0.47m - 0.66m
FixedLensFocalLength	525mm/20.669"
ProjNativeOffset	124%
<b>Connectivity</b>	
Connections	<b>Inputs</b> 3 x HDMI 2.0 <b>Outputs</b> 1 x S/PDIF, 1 x USB-A power 1.5A, 1 x Audio 3.5mm <b>Control</b> 1 x RS232
<b>General</b>	
NoiseLevelTypicalDb	26
NoiseLevelMaxDb	28
PcCompatibility	UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
Proj2DCompatibility	480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz)
Proj3DCompatibility	Frame Packing(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz)
Proj3DType	3D ready
ProductSecurity	Security bar, Kensington Lock, Password protected interface
OSDLangs	11 languages: Dutch, English, French, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional)
OperatingConditions	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%
RemoteControl	Backlit home remote
SpeakerCount	2
SpeakerWatts	10
In the box	AC power cord Remote Basic user manual
Input lag	4.00ms
<b>Power</b>	
PowerSupply	100 ~ 240V, 50 ~ 60Hz
PowerConsumptionWattsStandby	0.5
PowerConsumptionWattsMin	144.5
PowerConsumptionWattsMax	241.5
<b>Weight and dimensions</b>	
ProductDimensions	576 x 383 x 130
Gross weight	12 kg
Net weight	8.9 kg

