

CinemaX D2+

4K UHD ultra short throw laser home projector



- **Breathtaking 4K UHD resolution with Laser Light Source**
- **Ultra short throw feature, 120" big screen in inches away**
- **Bright 3,000 lumens and stable output, achieves 1,800,000 : 1 Contrast.**
- **Superb gaming experience with extremely low 4ms Input Lag for 240Hz at 1080P**



CinemaX D2+ features 4K UHD resolution and supports eARC audio, offering the ultimate cinematic experience like no other. The ultra short throw technology allows you to enjoy up to 120" screen in just inches away. With Amazing Color and 121% of Rec.709 gamut coverage, D2+ can deliver richer color performance and makes pictures even more realistic.

Specifications

Display/image	
Display technology	DLP™
Resolution	UHD (3840x2160)
Brightness	3,000 lumens
Contrast ratio	1,800,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3,16:9,16:10
Keystone correction - horizontal	10°
Keystone correction - vertical	10°
Horizontal scan rate	31 ~ 135Khz
Vertical scan rate	24 ~ 120Hz
Uniformity	90%
Screen size	2.16m ~ 3.05m (85" ~ 120") diagonal
Lamp info	
Light source type	Laser
LASER life	30,000 hours
Optical	
Throw ratio	0.25:1
Projection distance	0.47m - 0.66m
Focal length	525mm/20.669"
Native offset	124%
Connectivity	
Connections	Inputs 3 x HDMI 2.0 Outputs 1 x S/PDIF, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x RS232
General	
Noise level (typical)	26dB
Noise level (max)	28dB
PC compatibility	UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz)
3D compatibility	Frame Packing(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz)
3D	3D ready
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	11 languages: Dutch, English, French, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional)
Operating conditions	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%
Remote control	Backlit home remote
Speaker count	2
Watts per speaker	10W
In the box	AC power cord Remote Basic user manual
Input lag	4.00ms
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	144.5W
Power consumption (max)	241.5W
Weight and dimensions	
Dimensions (W x D x H)	576 x 383 x 130
Gross weight	12 kg
Net weight	8.9 kg

